

DESCRIPTION

Removes mineral type residues including cement and mortar residues, efflorescence, rust stains, general dirt and grime, hard water scale (limestone), grout haze and grout films.

USES

- Efflorescence
- Cement, mortar and grout residue
- Rust stains, mineral deposits and limescale
- General dirt and grime

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

- For external use only. Causes burns. DO NOT mix with other products.
- Keep children and animals away from the product and treated surfaces until rinsed off.
- Wear suitable clothing (gloves, eye protection and footwear) to prevent skin and eye contamination.
- If splashed in eyes rinse continuously with water. Remove contact lenses if possible. Seek medical attention or a poison center.
- Keep off all other surfaces, clothing and plants.
- Always test on a small, inconspicuous area first. This will allow you to establish how severe the soiling is and the best application method.
- DO NOT USE on acid sensitive surfaces such as limestone, marble, smooth cement, wet cast concrete slabs etc. TEST FIRST.
- Read the full instructions and Materials Safety Data Sheet available on Unilock.com.

INSTRUCTIONS

1. Sweep, vacuum or wipe the surface first.
2. Pre-wet the surface with clean water.
3. Dilute AcidClean as follows: LIGHT contamination: 1 part AcidClean to 10 parts water. MODERATE contamination: 1 part AcidClean to 5 parts water. HEAVY contamination: 1 part AcidClean to 3 parts water.
4. Apply to the pre-wetted surface with a sponge or mop.
5. Work in small areas.
6. Agitate with a long handled scrubbing brush or nylon pad.
7. Apply clean water and agitate with a brush.
8. Allow to set for no longer than 5-10 minutes.
9. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE.**
10. Remove dirty solution with a mop or wet vacuum cleaner.
11. Apply more clean water and agitate with a brush.
12. Remove with a mop or wet vacuum cleaner.
13. Repeat rinsing process as required.

LIMITATIONS

- DO NOT USE ON ACID SENSITIVE/POLISHED SURFACES such as limestone, marble, smooth cement, wet cast concrete slabs etc.;
- Do not mix with other cleaners or allow product to come in contact with any non-recommended surfaces.
- Acids of all kinds may etch, lighten, or change the colour of cementitious material, metallic glazes and some natural stones such as marble and limestone.

AcidClean

COVERAGE

COVERAGE 10-50 M2 PER LITRE for external use only. Causes skin burns. DO NOT mix with other products. BEFORE USE: Read precautions on the reverse of this bottle and the Materials Safety Data Sheet available at Unilock.com. For external use only. Causes skin burns. DO NOT mix with other products.

HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.
- Do not store next to foodstuffs and water supplies.
- Keep out of reach of children and animals.

SPILLAGES

Spills of up to 1 litre may be absorbed with paper towels. Spills of over 1 litre should be covered with a suitable absorbent, e.g. sand, earth or spill granules and collected for disposal. Label containers for disposal. The area contaminated by the spill should be washed thoroughly to remove residues.

FIRST AID

INHALATION - Remove from exposure. If breathing becomes difficult seek medical attention.
EYE CONTACT - hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a medical professional or a Doctor, or for at least 15 minutes. Remove contact lenses if possible.
SKIN CONTACT - remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.
INGESTION - rinse mouth with water and give a glass of water (200-300 ml) to drink. Do NOT induce vomiting. Seek immediate medical attention.

SAFETY DIRECTIONS

Wear protective clothing including overall, gloves and eye protection to prevent skin and eye contact. Open doors and windows to ensure good ventilation.

WARNING: Corrosive

R34 Causes severe burns;
S1/2 Keep locked up and out of the reach of children;
S26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice
S37/39 Wear suitable gloves and eye/face protection
S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible)

ALWAYS DO A TEST FIRST